

Service is in your authorization...

ML-122X Series Maxlogic Intelligent Addressable Fire Alarm Control Panels

In ML-122X series intelligent addressable panel and system; detectors, manual call points, loop-powered sounders, intelligent addressable loop-powered base sounder/sounder beacon, zone control modules and gas detectors can be programmed to work in cause&effect scenarios and fire automation can be done.

Fire alarm and fault information are shown in detail on the adjustable light intensity 240x64 graphic LCD screen on the panel. There are 4 different languages (Turkish, English, Russian, French) for the panel menu, serigraphy and Loop Manager + Lite software.



- ▶ Complies with EN 54-2 and EN 54-4 standards
- ▶ Supervised peripheral devices
- ▶ Advanced parametric arrangement options for input/output devices
- ▶ Top priority of fire alarm indication, different buttons for fire and other events, categorical classification due to events
- ▶ 1000 event log and 64 programmable zones memory
- ▶ Expandable up to 2 loops and 254 address capacity with modular structure



Addressing Device

Commissioning, Service and Maintenance Authorization for ML-122X Series

With Maxlogic intelligent addressable system ML-122X series fire alarm control panels, configuration software (LoopManager + Lite) and **Addressing Device, you can easily commission, service and maintain.**

- ▶ 4 different languages option (Turkish, English, Russian, French)
- ▶ User friendly, easy installation and use with aesthetic design
- ▶ Communication interrupt for fast fire detection in 1.5 sec
- ▶ The key is needed for entry to panel menu
- ▶ Day and night mode, pre-alarm, contamination warning

PANEL MODELS ACCESSORIES and OPTIONS MODULE MODELS

Product Code Description

| | |
|---------|--|
| ML-1221 | Fire alarm panel, 1 loops, 127 address |
| ML-1222 | Fire alarm panel, 2 loops, 254 address |

Product Code Description

| | |
|---------|---|
| ML-1613 | Intelligent addressable system LoopManager + Lite software |
| ML-1010 | Addressing device |
| ML-5200 | Loop test device |

Product Code Description

| | |
|-------------|--|
| ML-1361 | Relay control module, 1-way output |
| ML-1361.SCI | Relay control module, 1-way output, with short circuit isolator |
| ML-1362 | Switch monitor module, 1-way input |
| ML-1362.SCI | Switch monitor module, 1-way input, with short circuit isolator |
| ML-1363 | 2/1 I/O module (2 inputs / 1 output) |
| ML-1363.SCI | 2/1 I/O module (2 inputs / 1 output), with short circuit isolator |
| ML-1366 | 4/2 I/O module (4 inputs / 2 outputs) |
| ML-1366.SCI | 4/2 I/O module (4 inputs / 2 outputs), with short circuit isolator |
| ML-1371 | Sounder control module, 1-way output |
| ML-1371.SCI | Sounder control module, 1-way output, with short circuit isolator |

DETECTOR MODELS

Product Code Description

| | |
|-------------|---|
| ML-1110 | Optical smoke detector |
| ML-1130 | Heat detector |
| ML-1130BS | Class BS heat detector with mounting base |
| ML-1140 | Multi-sensor detector |
| ML-1110.SCI | Optical smoke detector, with short circuit isolator |
| ML-1130.SCI | Heat detector, with short circuit isolator |
| ML-1140.SCI | Multi-sensor detector, with short circuit isolator |

MANUAL CALL POINT MODELS

Product Code Description

| | |
|-------------|--|
| ML-1710 | Manual call point, resettable |
| ML-1710.SCI | Manual call point, resettable, short circuit isolator |
| ML-1730 | Manual call point, weatherproof (IP67), resettable |
| ML-1730.SCI | Manual call point, weatherproof (IP67), resettable, short circuit isolator |

SOUNDER MODELS

Product Code Description

| | |
|-------------|---|
| ML-1460 | Sounder & beacon, weatherproof (IP33) |
| ML-1460.SCI | Sounder & beacon, weatherproof (IP33), short circuit isolator |
| ML-1470 | Sounder, weatherproof (IP65) |
| ML-1470.SCI | Sounder, weatherproof (IP65), short circuit isolator |
| ML-1480 | Beacon, weatherproof (IP65) |
| ML-1480.SCI | Beacon, weatherproof (IP65), short circuit isolator |
| ML-1490 | Sounder & beacon, weatherproof (IP65) |
| ML-1490.SCI | Sounder & beacon, weatherproof (IP65), short circuit isolator |

SOUNDER MODELS

Product Code Description

| | |
|-------------|--|
| ML-1410 | Sounder |
| ML-1410.SCI | Sounder with short circuit isolator |
| ML-1420 | Beacon |
| ML-1420.SCI | Beacon with short circuit isolator |
| ML-1430 | Sounder & beacon |
| ML-1430.SCI | Sounder & beacon with short circuit isolator |
| ML-1440 | Sounder, weatherproof (IP33) |
| ML-1440.SCI | Sounder, weatherproof (IP33), short circuit isolator |
| ML-1450 | Beacon, weatherproof (IP33) |
| ML-1450.SCI | Beacon, weatherproof (IP33), short circuit isolator |

MODULE MODELS

Product Code Description

| | |
|-------------|---|
| ML-1372 | Zone monitor module, 1-way input |
| ML-1372.SCI | Zone monitor module, 1-way input, with short circuit isolator |
| ML-1373 | 2/1 I/O module (2 inputs / 1 output) |
| ML-1373.SCI | 2/1 I/O module (2 inputs / 1 output), with short circuit isolator |
| ML-1380 | Short circuit isolator module |